

DETAIL OF PIERS AT FR. 10
DETAIL OF PIERS AT FR. 76
DETAIL OF PIERS AT FR. 45
DETAIL OF PIERS AT FR. 54
SECTION IN WAY OF INBOARD PROPELLERS
SECTIONS AT FRS. 180-185
FRAME SPACING 4'-0"
LENGTH BETWEEN PERPENDICULARS = 860'-0"
CAUTION
BLOCKS IN WAY OF RUDDER AND PROPELLERS TO BE REMOVED TO PREVENT DAMAGE WHILE DOCKING DUE TO TRIM OF SHIP.
1 ST. DOCKING POSITION
2 ND. DOCKING POSITION
3 RD. DOCKING POSITION
BOTTOM OF KEEL
ARRANGEMENT OF PIERS SHOWING THE THREE SUCCESSIVE DOCKING POSITIONS OF VESSEL
DIAGRAMMATIC LONGL. SECTION THRU FLAT KEEL
SECTION AT FR. 10
PRINCIPAL DIMENSIONS
GENERAL NOTES
OFFSETS FOR DOCKING
REFERENCES
ALTERATIONS
PRELIMINARY
BB61-U.S.S. IOWA
BB62-U.S.S. NEW JERSEY
BB63-U.S.S. MISSOURI
BB64-U.S.S. WISCONSIN
BB65-
BB66-
DOCKING PLAN
PLANNING DIVISION
NAVY YARD, NEW YORK
DRAWN BY
CHECKED BY
TRACED BY
IN CHARGE
SCALE
PRINCIPAL NAVAL ARCHITECT
APPROVED
DATE
ASSISTANT DESIGN SUPERINTENDENT
N.Y.N.Y. No. BB61-0700AA
BASIC C.&R. No. 351753
0700AA
150,553
1400-9.2-61



CAUTION

BLOCKS IN WAY OF RUDDER AND PROPELLERS TO BE REMOVED TO PREVENT DAMAGE WHILE DOCKING DUE TO TRIM OF SHIP.



OFFSETS FOR DOCKING

FR.	H.B. SHELL SIGHT EDGES LOWER C	UPPER C	LOWER E	UPPER E	LONG'L. № 3 H.B.	H.B. TORPEDO BHDS. № 3	№ 2	TANGENCY H.B.	BILGE KEEL OUTER EDGE H.B.	HTS.
4								3-7-3+		
6								4-2-3		
8								4-9-2+		
10								5-3-6+		
12								5-10-2		
14								6-4-4		
16								6-10-5		
18								7-4-3		
20							7-1-6	7-9-4		
22			6-7-0					8-1-7+		
24								8-5-6		
26								8-9-1		
28							7-1-6	8-11-7		
30							7-4-0	9-2-3+		
32							7-6-1+	9-4-6		
34				13-11-7+			7-8-3+	9-7-1		
36			6-7-0	14-7-4+		5-2-7	7-10-6	9-9-4		
38			7-4-3+	15-3-5		6-3-6	9-1-1+	10-0-1		
40			8-1-7	15-11-6		7-4-5	10-3-5	10-3-0		
42			8-11-2+	16-8-6		8-5-4	11-6-0	10-6-1+		
44			9-11-5+	17-6-1+		9-6-3	12-9-3	10-9-6		
46			9-5-0+	18-4-4+	5-3-2	10-7-2	14-1-7+	11-1-7		
48			10-6-3+	19-3-2	5-6-2	11-8-1	15-6-3+	11-7-0		
50	4-3-0	7-4-5+	11-7-5+	20-2-3	5-9-2	12-9-0+	16-10-7	12-1-0		
52	4-3-0	8-4-7	12-8-7+	21-1-6+	6-6-6	14-0-2	18-3-1+	12-8-2		
54	4-4-2	9-5-0	13-10-2+	22-1-2+	7-4-2	15-3-3	19-7-3+	13-4-4+		
56	5-2-2	10-5-1+	14-11-5	23-1-3	8-1-6	16-6-4	20-10-7	14-2-0		
58	6-0-2	11-5-3	16-1-0	24-1-2+	8-11-2	17-9-5	22-2-4	15-0-6		
60	6-10-2	12-5-1+	17-2-2+	25-1-5	9-8-6	19-0-6	23-5-5+	16-0-4		
62	5-5-0+ (P) 7-8-2 (S)	13-4-2	18-3-5	26-1-6	10-6-2	20-3-6	24-8-7+	17-1-2		
64	6-1-5	14-3-2+	19-4-7+	27-1-4	11-3-6	21-6-6+	25-9-1	18-2-6		
66	6-10-1+	15-2-3+	20-6-2+	28-1-2	12-1-2	22-6-7+	26-9-2	19-4-5		
68	7-6-5+	16-1-4	21-7-1	29-0-5	12-10-6	23-4-2+	27-9-2	20-7-0		
70	8-3-2	17-0-4+	22-4-1	29-11-5+	13-8-2	24-1-5	28-6-0	21-9-6+		
72	8-11-6+	17-11-5+	23-1-1	30-10-5+	14-5-6	24-11-0	29-2-4	23-1-4		
74	12-5-6	18-10-6	23-10-1	31-9-1	15-3-2	25-8-4	29-11-2	24-5-5		
76	13-3-0	19-9-6+	24-7-1	32-7-1	16-0-6	26-5-7+	30-8-0	25-10-2		
78	14-0-2	20-5-4	25-4-1	33-4-3+	16-10-2	27-3-3+	31-4-7	27-3-2		
80	14-6-6+	20-11-1	26-1-1	34-1-0	17-4-1	28-1-1	32-1-7+	28-8-5		
82	14-9-0+	21-4-5+	26-10-1	34-8-5	17-6-3	28-10-5+	32-10-7	30-2-2		
84	14-11-2+	21-10-2+	27-7-1	35-2-7	17-8-5	29-8-2	33-8-1+	31-8-0		
86	15-1-4+	22-3-7	28-4-1	35-7-6	17-10-7	30-5-6	34-5-3	33-1-5		
88	15-3-6	22-8-1+	29-0-3	36-0-3+	18-1-1	31-1-6	34-10-7+	34-6-5		
90	15-6-0	22-11-6	29-3-4+	36-4-5+	18-3-3	31-4-7+	35-0-4+	35-11-4	49-4-7	7-11-7
92	15-8-2	23-3-2	29-6-5+	36-8-3+	18-5-5	31-8-1	35-2-2	37-3-2+	50-9-7	6-4-1
94	15-10-3+	23-6-6+	29-9-6+	36-11-6	18-7-7	31-11-2+	35-3-7	38-7-1	51-2-7+	5-2-0
96	16-0-5+	23-10-2+	30-0-7+	37-3-1	18-10-1	32-2-4+	35-6-7	39-10-3	51-6-1+	4-2-5
98	16-2-7+	24-1-7	30-4-1	37-6-4	19-0-3	32-5-6	35-10-0	41-1-1	51-9-1+	3-4-2+
100	16-5-1+	24-5-3	30-7-2	37-9-7	19-2-5	32-8-7+	36-1-1	42-3-0+	52-0-0+	2-7-0+

FR.	H.B. SHELL SIGHT EDGES LOWER C	UPPER C	LOWER E	UPPER E	LONG'L. № 3	H.B. TORPEDO BHDS. № 3	№ 2	TANGENCY H.B.	INB'D. HEEL OF TWIN KEELS H.B.	BILGE KEEL OUTER EDGE H.B.	HTS.
102	16-6-0	24-8-7+	30-10-3	38-1-1+	19-4-7	33-0-1	36-4-2	43-4-1		52-2-6+	1-10-2+
104		25-0-0	31-1-4+	38-4-4+	19-6-0	33-3-2+	36-7-3	44-4-0		52-5-4	1-2-3
106			31-4-5+	38-7-7+		33-6-4	36-10-4	45-2-2		52-8-0+	0-7-3+
108			31-7-6+	38-11-2		33-9-6	37-1-5	45-11-1+		52-8-7	0-3-1+
110			31-10-7+	39-2-5		34-0-7+	37-4-6	46-6-4		52-7-5	0-3-0
112			32-2-1	39-6-0		34-4-1	37-7-7	47-0-2+		52-7-3	
114		25-0-0	32-5-2	39-9-2+		34-7-2+	37-11-0	47-4-2		52-9-0	
116		25-1-3+	32-8-0	40-0-5+		34-10-4+	38-2-1	47-6-7		53-0-2	
118		25-3-5+		40-4-0+		35-0-7+	38-5-2	47-8-3		53-4-3	0-3-0
120		25-6-0		40-7-0			38-6-6+	47-9-1+		53-8-5	0-4-2
122		25-8-2+						47-9-0+		53-10-4	0-8-7+
124		25-10-4+						47-8-1+		53-11-2	1-3-3
126		26-0-7						47-5-7+			1-10-4
128	16-6-0	26-3-1						47-1-6			2-5-6+
130	16-7-0	26-2-6+						46-7-2			3-1-1+
132	16-8-4+	26-0-7+						45-10-4			3-8-4
134	16-10-1+	25-11-0						44-11-7			4-3-6+
136	16-11-6	25-9-1		40-7-0			38-6-6+	43-11-5+			4-10-5
138	17-1-2+	25-7-1+		40-8-1+			38-7-5	42-10-0			5-5-0
140	17-2-7+	25-5-2+		40-9-3+		35-0-7+	38-8-7	41-6-5+	17-5-4		5-11-2+
142	17-0-3	25-3-3+		40-10-3+		35-1-1	38-10-3	40-1-3+	17-0-3	53-11-2	6-5-3+
144	16-7-3+	25-1-4		40-11-1		35-1-3	39-0-3	38-6-5	16-7-3+	53-9-7+	7-0-2
146	16-2-4+	24-11-5		40-11-2+		35-1-5	39-2-3	36-10-3	16-2-4+	53-4-1+	7-8-4+
148	15-9-7	24-9-5+		40-10-7+		35-2-4+	39-4-7+	35-1-5	15-9-7	52-4-3	8-6-2
150	15-5-2	24-7-6+		40-10-2		35-5-6+		33-4-7	15-5-2	49-6-5	9-11-2
152	15-0-6+	24-5-7+	32-8-0	40-9-1		35-5-6+		31-8-1	15-0-6+		
154	14-8-4	24-4-0	32-7-7+	40-7-2+				29-11-5	14-8-4		
156½	14-3-1	22-9-4	32-7-1	40-3-6+				27-11-3	14-3-1		
158½	13-10-7+	22-5-4						26-5-0+	13-10-7+		
160½	13-6-6	22-1-4						25-0-0	13-6-6		
162½	13-2-6	21-9-4						23-8-0+	13-2-6		
164½	12-10-7+	21-5-4						22-5-2	12-10-7+		
166	12-8-1+	22-3-5			19-6-0			21-7-0	12-8-1+		
168	12-4-5	21-3-4+			18-9-4			20-5-2	12-4-5		
170	12-1-2	20-4-3			18-1-0			19-4-6+	12-1-2		
172	11-10-0	19-9-7+			17-4-4			18-5-1	11-10-0		
174	11-7-1	19-2-6			16-8-0+			17-6-4	11-7-1		
176	11-4-4+				15-11-6			16-8-6+	11-4-4+		
178	11-2-3+				15-3-3+			16-0-1	11-2-3+		
180	11-0-6+				14-7-1			15-4-3+	11-0-6+		
182								14-9-5+	10-11-5		
184								14-3-4+	10-10-6+		
186								13-10-0	10-10-2+		
188								13-4-4+	10-10-0+		
190								12-11-1	10-10-0+		
192								12-5-3	10-10-1		
194											
196											

PRINCIPAL DIMENSIONS

LENGTH OVER ALL (MOLDED) ----------

LENGTH BET. PERPENDICULARS ---------- 860'-0"
AT DESIGNED W.L. (34'-9¼" ABOVE BOTTOM OF KEEL)

LENGTH OVER ALL ----------
TAKEN FROM WORK

BREADTH EXTREME TO OUTSIDE OF PLATING ------ APPROX. 108'-3"
(EXACT DIMENSION TO BE TAKEN FROM COMPLETED VESSEL)

DISPLACEMENT NORMAL ----------

DRAFT AT NORMAL DISPLACEMENT ----------

FRAME SPACING ---------- 4'-0"

⦶ IS 24" AFT OF FRAME 107.

GENERAL NOTES

1.– ALL VERTICAL DIMENSIONS ARE GIVEN ABOVE BOTTOM OF KEEL PLATE AMIDSHIPS.

2.– ALL DRAFT MARKS ARE MEASURED FROM A DATUM LINE, 2" BELOW MOLDED BASE LINE OF SHIP, THE 2" REPRESENTING THE THICKNESS OF FLAT KEEL AMIDSHIPS.

3.– ALL ATHWARTSHIP DIMENSIONS ARE HORIZONTAL HALFBREADTHS AND NOT GIRTHS.

4.– CENTERLINE BLOCKING TO BE ARRANGED IN PIERS OF THREE 14" BLOCKS EACH, THRUOUT THE LENGTH OF KEEL, WITH CLEAR DISTANCE OF 30" BETWEEN PIERS. SIDE PIERS ARRANGED OPPOSITE CENTERLINE PIERS.

5.– FOR 1ST DOCKING: FRAME № 100 (DATUM FRAME) IS PLACED OVER ℄ OF A THREE BLOCK PIER.
FOR 2ND DOCKING: FRAME № 100 IS PLACED 24" FORWARD OF ℄ OF PIER.
FOR 3RD DOCKING: FRAME № 100 IS PLACED 24" AFT OF ℄ OF PIER.
THIS SHIFT IN THREE SUCCESSIVE DOCKINGS PERMITS ACCESS TO ENTIRE SHELL OF VESSEL FOR PRESERVATION WORK. THEREAFTER THE CYCLE IS REPEATED FOR OTHER DOCKINGS.

6.– HARD CAP BLOCKS OF NOT LESS THAN SIX INCHES THICK TO BE USED THRUOUT.

7.– AT LEAST FOUR PIERS WHERE THE PIVOTING LOADS ON LANDING AND LIFTING WILL COME, ARE TO BE CRIBBED TO INSURE STABILITY OF THE BLOCKS AGAINST TIPPING.

8.– ONE OR MORE PIERS SHALL BE SET FORWARD AND AFT OF ALL KEELS TO INSURE SUPPORT IN CASE THE VESSEL IS LANDED FORWARD OR AFT OF THE POSITION INTENDED.

9.– OUTBOARD PIERS UNDER "E" STRAKE P/S TO BE REARRANGED FOR 2ND & 3RD DOCKING POSITIONS TO CLEAR WING TANK OPENINGS.

10.– INSPECT THE RUDDER AND OTHER HOLLOW APPENDAGES IN ACCORDANCE WITH ART. 1122 OF THE CONSTRUCTION & REPAIR MANUAL. IF EVIDENCE OF LEAKAGE EXISTS, REPAIR & AIR TEST IN ACCORDANCE WITH ART. 627 OF THE C.& R. MANUAL.

11.– WHEN THE PIER SYSTEM IS NOT AVAILABLE FOR THE SIDE DOCKING KEELS, THE BLOCKS SHALL BE SPACED 2'-0" CENTERS WITH 15 FEET OF SOLID PACKING AT EACH END.

12.– ALL DIMENSIONS SUBJECT TO FINAL CHECK FROM VESSEL WHEN IN DRY DOCK.

ALTERATIONS

MARK	PANEL	MADE BY	CH'K'D BY	DESCRIPTION	APP'D BY	DATE

REFERENCES

1. GENERAL SPECIFICATIONS - APPENDIX 16.
2. BU. C.& R. LET. № N16-8 (DF) EN7/A2-11 OF SEPT. 9, 1937.
3. " " " " " " S7/S1-3 (TB) EN7/A2-11 OF APRIL 9, 1938.
4. " " " " " " N16-8 (TB) EN7/A2-11 OF MAR. 23, 1939.
5. BU. C.& R. MEMO OF MARCH 23, 1939. "DRY DOCK BLOCKS."
6. BU. C.& R. LET. № S7/S1-3 (DS) EN7/A2-11 OF JAN. 15, 1940.

PRELIMINARY

BB61-U.S.S. IOWA | BB64-U.S.S. WISCONSIN
BB62-U.S.S. NEW JERSEY | BB65-
BB63-U.S.S. MISSOURI | BB66-

DOCKING PLAN

PLANNING DIVISION
NAVY YARD, NEW YORK

DRAWN BY ______ CHECKED BY ______
TRACED BY ______ IN CHARGE ______
SCALE: ______ PRINCIPAL NAVAL ARCHITECT

APPROVED
DATE: ______ ASSISTANT DESIGN SUPERINTENDENT

N.Y. N.Y. № BB616-0700AA

BASIC C.& R. № 351753

0700AA

150,553

1400-9.2-61